
# **GREAT TECHNOLOGY**

# Antarctica Coolneess Catalog
















































# Attractive Design

It provides easy access to the comfort you desire through its attractive design.

Equipped with the best technologies, Rota Climate Seal makes your life easier with its power and aesthetics.

**Design Team** 

# Climate is under your control

Air conditioning is in your control due to Rota Climate's high technology.

































Self Cleaning Feature



**25dB** Ultra Quiet Operation



60% energy saving R32 Refrigerant



# With inverter technology A+++ Energy efficiency.

The inverter is a technology that provides more efficiency and comfort by changing the operating frequency of the engine.





## Wide Wing

Wide wings angle comfort spreads, throughout the room





# WiFi Technology\*

You can air conditon your room remotel

\*WiFi Feature is optional.



It provides powerful performance with just pressing a key.



Powerful mode

Provides stronger performance with one click cools room fast, heats fast



## **Comfort Sleep Mode**

Overheating and overcooling are avoided during the night by activating the Comfort Sleep Mode with the OFF key



































9000 BTU/h Cooling (max) : 11.600 BTU/h Heating (max) : 11.500 BTU/h

12000 BTU/h Cooling (max) : 13.400 BTU/h Heating (max) : 14.200 BTU/h

18000 BTU/h Cooling (max) : 21.000 BTU/h Heating (max) : 23.000 BTU/h

**24000 BTU/h**Cooling (max): 27.000 BTU/h
Heating (max): 27.000 BTU/h



# Macaroni

# Feel the Difference Instantly

Equipped with innovative and advanced technology, Macaroni is designed entirely for your comfort.

Your device, which provides a clear airflow and makeds your living space more enjoyable with its superior qualitry, offers long-lasting and reliable performance, allowing you to enjoy Rota Climate for many years.

# Complete Comfort

Meet the comfort of silence. With macaroni, where you can experience modern technology in the most effective way, you'll enjoy tranquility whether you're relaxing or working in a quiet environment.

While your device maintains the ideal temperature in any space you desire, it also ensures energy efficiency.

# Climate is under your control

Air conditioning is in your control due to Rota Climate's high technology.



























Technology Team



Self Cleaning Feature



**25dB** Ultra Quiet Operation



60% energy saving R32 Refrigerant



## With inverter technology A+++ Energy efficiency.

The inverter is a technology that provides more efficiency and comfort by changing the operating frequency of the engine.





## Wide Wing

Strong Mode

Wide wings angle comfort spreads, throughout the room

It provides powerful

performance with just pressing a key.







Powerful mode



#### WiFi Technology\*

You can air conditon your room remotel

\*WiFi Feature is optional.



## **Comfort Sleep Mode**

Overheating and overcooling are avoided during the night by activating the Comfort Sleep Mode with the OFF key



Gold Plating Technology



Antarctica Coolness

































# Experience the new design with superior technology.

Reindeer, which has won admiration with its new design, will suit very well every area where it is used. Reindeer, the new technology that keeps you comfortable in all seasons with perfect climate control, is designed to make your life better.

You can immediately become acquainted with this technology that is environmentally friendly with its energy and considers your budget.







# Silent as the Poles

Combining quality, comfort and technology, Reindeer provides comfortable air flow with its ultraquiet operation feature, and only the sounds you love be with you in your home or workplace.



# Climate is under your control

Air conditioning is in your control due to Rota Climate's high technology.







Cooling (max): 14.200 BTU/h Heating (max): 16.300 BTU/h

### 18000 BTU/h

Cooling (max): 21.400 BTU/h Heating (max): 23.900 BTU/h



























Technology Team



**25dB** Ultra Quiet Operation



60% energy saving R32 Refrigerant



# With inverter technology A+++ Energy efficiency.

The inverter is a technology that provides more efficiency and comfort by changing the operating frequency of the engine.





## Wide Wing

Wide wings angle comfort spreads, throughout the room





# WiFi Technology You can air conditon your room remotel



It provides powerful performance with just pressing a key.




Powerful mode

## **Comfort Sleep Mode**

Overheating and overcooling are avoided during the night by activating the Comfort Sleep Mode with the OFF key











### All flare connections, the easiest VRF to install

Mini VRF system uses all flare connection which can greatly simplify installation. The multiple branch header with 1 to 2,3,4,5 or 6 options further simplify installation.




### 1 to 9 Indoor Units Connection

A single outdoor unit supports 1 to 9 indoor units, freeing up considerable space outside. Use your backyard more wisely with much more space available created by less number of outdoor units.




### Long Piping Lenght

Mini VRF provides a total piping lenght possibilty of 130m, a maximum height difference between outdoor and indoor units of 30m. The height difference between indoor units can be up to 10m. These generous allowances facilitate an extensive array of system designs.



# Centralized Control with Other VRF System, Convenient for Unified Management

Mini VRF series system and other VRF system with up to 64 indoor units and 8 system can be controlled in one centralized control system, it is very convenient for administrators to manage equipment uniformly.





# Monoblock


































# **Features**












# **Application**

A complete, All-Year-Round Solution

- Space Cooling
- Space Heating
- Domestic Hot Water







RotaClimate HP series offers flexibility in that its hydraulic components can be installed either indoors or outdoors. In the RotaClimate HP-Mono model, the hydronic components are integrated into the outdoor unit.

This provides the advantage of easy and practical installation, offering more flexibility and alternative solutions in mounting.

It has an A+++ class in energy efficiency and makes a significant contribution to reducing environmental impacts.

# GREAT TECHNOLOGY

Antarctica Coolness









42000BTU
Cooling 42000 BTU max
Heating 47000 BTU max



48000BTU

Cooling 50000 BTU max
Heating 64000 BTU max





technology.

Technology Team





# **Energy Saver**



# **Strong Mode**

It provides powerful performance with just pressing a key.



# **Comfort Sleep Mode**

Overheating and overcooling are avoided at night by activating the Comfort Sleep Mode with the OFF key.



# Vertical Wings Wide Comfortable Spaces



## **34dB**

Ultra Quiet Operation



## **Energy saving**



## **Monophase Electric**

Working at home or in the office comfortably with a 220W power line



#### **Bio Filter**

BioFilter blocks harmful bacteria and keeps the air clean and fresh.













practical with its compact and modern design for occupied spaces.

**Design Team** 



Whether at Home,
Whether in the Office,
Whether in the Home Office

# 12000 BTU

Panda is a powerful air conditioner for occupied spaces due to its capacity.



The least energy-consuming air conditioner in its class with Panda Energy efficiency



# (zz Comfort Sleep Mode

Overheating and overcooling are avoided at night by activating Comfort Sleep Mode with the OFF key.



# Mobile

You can easily control the climate of indoor places whenever and wherever you want with its mobile feature.

## **BioFilter**

BioFilter blocks harmful bacteria and keeps the air clean and fresh.



## 24 hour timer

It can be turned ON or OFF anytime you wish by activating the timer.



































# under your control

Air conditioning is in Rota Climate's high technology.

**Technology Team** 





360°)

























29dB Ultra Quiet Operation



# **Wind Wings**

Wide Comfortable Spaces



## **Bio Filter**

BioFilter blocks harmful bacteria and keeps the air clean and fresh.



60% energy saving R32 Refrigerant



# **Comfort Sleep Mode**

Overheating and overcooling are avoided at night by activating Comfort Sleep Mode with the OFF key.



## **Strong Mode**

It provides powerful pressing a key. Performance with just



# Duct type air conditioning

























Rota Climate's high technology.































29dB Ultra Quiet Operation



# **Wind Wings**

Wide Comfortable Spaces



## **Bio Filter**

BioFilter blocks harmful bacteria and keeps the air clean and fresh.



60% energy saving R32 Refrigerant



# **Comfort Sleep Mode**

Overheating and overcooling are avoided at night by activating Comfort Sleep Mode with the OFF key.



## **Strong Mode**

It provides powerful pressing a key. Performance with just



Antarctica Coolness



























## M2-18 OD

18 BTU 2+1 DIŞ ÜNİTE	2 İÇ ÜNİTE	9+9	9+12	12+12
----------------------	------------	-----	------	-------

#### M3-28 OD

28 BTU 3+1 DIS ÜNİTE	2 İÇ ÜNİTE	9+9	9+12	9+18	12+12	12+18
20 BTO 3+1 DIŞ UNITE	3 İÇ ÜNİTE	9+9+9	9+9+12	9+12+12	12+12+12	

#### M4-36 OD

	2 IÇ UNITE	9+24	12+24	18+18	18+24				
36 BTU 4+1 DIŞ ÜNİTE	3 İÇ ÜNİTE	9+9+18	9+9+24	9+12+18	9+12+24	9+18+18	12+12+18	12+12+24	12+18+18
	4 İÇ ÜNİTE	9+9+9+9	9+9+9+12	9+9+9+18	9+9+12+12	9+9+12+18	9+12+12+12	12+12+12+12	

#### M5-42 OD

	3 İÇ ÜNİTE	12+18+24	18+18+18			
42 BTU 5+1 DIŞ ÜNİTE	4 İÇ ÜNİTE	9+9+12+24	9+9+18+18	9+12+12+18	12+12+12+18	
	5 İÇ ÜNİTE	9+9+9+9+9	9+9+9+9+12	9+9+9+9+18	9+9+9+12+12	9+9+12+12+12







ROTA M	odel Name - Indoor		SEAL09ID	SEAL12ID	SEAL18ID	SEAL24ID
ROTA Mo	odel Name - Outdoor		SEAL09OD	SEAL12OD	SEAL180D	SEAL24OD
	Indoor code		22022011012298	22022011013881	22022011012358	22022011012359
	outdoor code		22022016015240	22022016015140	22022016016840	22022016016820
Power supply		V-Ph-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Rated Cooling	Capacity	Btu/h	9000(3100~11600)	12000(3800~14200)	18000(6200~21000)	24000(7100~27000)
Cooling Power input		w	732(100~1240)	1213(130~1580)	1550(140~2300)	2600(420~3150)
Cooling Current		А	3.18(0.4~5.4)	5.27(0.5~6.9)	6.7(0.6~10)	11.5(1.8~13.8)
Rated Heating	Capacity	Btu/h	10000(2800~11500)	13000(3700~14400)	19000(4400~23000)	25000(5500~27000)
Heating Power input		w	733(120~1200)	1088(100~1680)	1570(220~2350)	2400(300~2750)
Heating Current		А	3.18(0.5~5.2)	4.73(0.4~6.9)	6.8(0.95~10.2)	11(1.3~12.2)
	Pdesigno	kW	2.8	3,5	5,3	7.0
Seasonal Cooling	SEER	w/w	6.2	6.1	6,7	6.1
	Energy Efficiency Class		A++	A++	A++	A++
		kW	2.6	2,6	4.1	5,1
	Pdesignh	-				
Heating(Average )	SCOP	W/W	4.0	4.0	4,1	4.0
	Energy Efficiency Class	H	A+	A+	A+	A+
T-1	Tbiv	°C	-7	-7	-7	-7
Tol		°C	-15	-15	-15	-15
Max. input consumption		w	2150	2150	2500	3500
Max. current	1	A	10	10	13	15.5
Compressor	Туре		ROTARY	ROTARY	ROTARY	Twin-ROTARY
Indoor air flow (Hi/Mi/Lo)		m3/h	466/360/325	540/430/314	840/680/540	980/817/662
Indoor sound pressure level (Hi/N	Mi/Lo/Si)	dB(A)	38.5/32/25/21	40.5/34.5/25/21.0	42.5/36/26/20	45/40.5/36/29.5
Indoor sound power level (Hi)		dB(A)	52	52	55	59
	Dimension(W*D*H)	mm	805x194x285	805x194x285	957x213x302	1040x220x327
Indoor unit	Packing (W*D*H)	mm	870x270x365	870x270x365	1035x295x385	1120x405x315
	Net/Gross weight	Kg	7.6/9.7	7.6/9.8	10/13	12.3/15.8
Outdoor air flow		m3/h	1750	1800	2100	3500
Outdoor sound pressure level		dB(A)	55.5	56.0	56	59
Outdoor sound power level		dB(A)	61	62	63	65
	Dimension(W*D*H)	mm	720x270x495	720x270x495	805x330x554	890x342x673
Outdoor unit	Packing (W*D*H)	king (W*D*H) mm	835x300x540	835x300x540	835x300x540 915x370x615	
	Net/Gross weight	Kg	23.2/25.0	23.2/25.0	32.7/35.4	42.9/45.9
	Туре		R32	R32	R32	R32
Refrigerant	GWP		675	675	675	675
	Charged quantity	Kg	0.55	0.55	1.08	1.42
Design pressure	Į.	MPa	4.3/1.7	4.3/1.7	4.3/1.7	4.3/1.7
	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/12.7mm(1/2in)	9.52mm(3/8in)/15.9mm(5/8
Refrigerant piping	Max. refrigerant pipe length	m	25	25	30	50
	Max. difference in level	m	10	10	20	25
Connection wiring			1.5x5//	1.5x5//	1.5x5//	2.5x5//
Plug type			1.5x3/no-plug	1.5x3/no-plug	//no-plug	//no-plug
Thermostat type			Remote Control	Remote Control	Remote Control	Remote Control
2,000	Indoor(cooling/ heating)	*C	17 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30
Operation temperature	Outdoor(cooling/heating)	°C	-15 ~ 50/-15 ~ 30	-15 ~ 50/-15 ~ 30	-15 ~ 50/-15 ~ 30	-15~50/-15~30
Application		_				
Application area	minimum-maximum	m2	12~18	16 ~ 23	24~35	32~47
Qty/per 20' /40' /40'HQ		-	132/274/305	132/274/305	84/180/208	66/137/156
Replacement (extra) heating capa		kW	0.0	0.0	0.0	0.0
Annual energy consuption (Coolin	1	kWh/year	156 / 714	221 / 686	247 / 1208	405 / 1691
Heating	P design	kW	2,6	2,5	4,4	5,8
Aegean, Mediterranean Region	SCOP	W/W	5,1	4,73	5,1	4,8
	Energy Efficiency Class		A+++	A+++	A+++	

\*Leakage in refrigerants causes climate change. Material that has refrigerants with lower gobal warming potential (GWP) contribute less to global warming if they leak into the atmosphere than materials that have refrigerants

higher GWP. This device contains refrigerant liquid has GWP equal to [xxx], in case of the coolant liquid in question leakage into the atmosphere, means that the impact on global warming will be [xxx] times greater than 1 kg (xxx) of 2 over a 100-year period. Never interfere with the refrigerant circuit or attempt to disassemble the product yourself, and always consult an expert.

ater than Tikg CO 2 over a Tub-year pendo. Never interiere with the ferrigerant circuit or attempt to disassemble the product yourself, and always consult an energy consumption according to standard test results. Actual energy consumption will vary depending on how the device is used and where it is located.







Model		_	Macaroni 9	Macaroni 12	Macaroni 18	Macaroni 24
Indoor			MACARONI 9 IDU	MACARONI 12 IDU	MACARONI 18 IDU	MACARONI 24 IDU
Outdoor			MACARONI 9 ODU	MACARONI 12 ODU	MACARONI 18 ODU	MACARONI 24 ODU
Power Supply		Ph-V-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Cooling Capacity		Btu/h	9000(3100~11600)	12000(3800~13400)	18000(6200~21000)	24000(7100~27000)
Working Power (Cooling)		W	800(100~1240)	1320(83~1600)	1550(140~2300)	2600(420~3150)
Working Current (Cooling)		Α	3.48(0.4~5.4)	5.8(0.8~7.3)	6.7(0.6~10)	11.5(1.8~13.8)
Heating Capacity		Btu/h	10000(2800~11500)	13000(3700~14200)	19000(4400~23000)	25000(5500~27000)
Working Power (Heating)		W	930(120~1200)	1190(167~1400)	1570(220~2350)	2400(300~2750)
Working Current (Heating)		Α	4.05(0.5~5.5)	5.3(1.4~6.4)	6.8(0.95~10.2)	11(1.3~12.2)
3 ( 3,	P design	kW	2.6	3.5	5.2	7.0
Seasonal Cooling	SEER	W/W	7.0	6.5	7.4	6.1
	Energy Efficiency Class	,	A++	A++	A++	A++
	P design	kW	2.3	2.8	4.1	4.8
Seasonal Heating	SCOP	W/W	4.1	4.1	4.0	4.0
(Avarage)	Energy Efficiency Class	,	A+	A+	A+	A+
	Design Temperature	°C	-7	-7	-7	-7
	P design	kW	2.3	3.0	4.4	5.8
Seasonal Heating	SCOP	W/W	5.1	5.2	5.1	4.8
(Aegean-Mediterranean Region)	Energy Efficiency Class	,	A+++	A+++	A+++	A++
	Design Temperature	°C	2	2	2	2
Annual Energy Consumption Q CE	Cooling	kWh/yıl	130	188	247	405
Annual Energy Consumption Q HE	Heating	kWh/yıl	792	958	1435	1680
Annual Energy Consumption	Cooling/Heating	kWh/yıl	130 / 666	188 / 823	247 / 1208	405 / 1691
Tol		°C	-15	-15	-15	-15
Max Input Production		W	2150	2150	2500	3500
Max Flow	T	Α	10	10	13	15.5
Compressor	Туре		ROTARY	ROTARY	ROTARY	Twin-ROTARY
Air Flow Rate (High-Medium-Low)		m3/h	435/333/259	530/430/310	840/680/540	980/817/662
Indoor UnitSound Pressure Level (H	li/Mi/Lo/Si)	dB(A)	37/32/25/21.5	39.5/35.5/25/21.5	42.5/36/26/20	45/40.5/36/29.5
Indoor UnitSound Power Level (Hi)	T	dB(A)	50	54	56	59
	Dimensions	mm	715x194x285	805x194x285	957x213x302	1040x220x327
Indoor Unit	Package Dimensions	mm	780x270x365	870x270x365	1035x295x385	1120x405x315
	Net/Gross Weight	Kg	6.7/8.8	7.3/9.5	10/13	12.3/15.8
Outdoor UnitSound Pressure Level		dB(A)	55	55	56	59
Outdoor UnitSound Power Level	T	dB(A)	59	64	63	67
	Dimensions	mm	720x270x495	720x270x495	805x330x554	890x342x673
Outdoor Unit	Package Dimensions	mm	835x300x540	835x300x540	915x370x615	995x398x740
	Net/Gross Weight	Kg	21/22.8	21/22.8	32.7/35.4	42.9/45.9
	Туре		R32	R32	R32	R32
Refrigerant	GWP		675	675	675	675
	Charged Guantity	Kg	0.47	0.52	1.08	1.42
	Liquid Side/Gas Side	mm(inch)		6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/12.7mm(1/2in)	9.52mm(3/8in)/15.9mm(5/8in)
Refrigerant Pipes	Maximum Pipe Length	m	25	25	30	50
	Maximum Height Difference	m	10	10	20	25
Wiring Type			1.5x5//	1.5x5//	1.5x5//	2.5x5//
Plug Type			//no-plug	//no-plug	//no-plug	//no-plug
Thermostat Type			Remote Control	Remote Control	Remote Control	Remote Control
Working Tomporature	Indoor (Cooling/Heating)	°C	17~32/0~30	17~32/0~30	17~32/0~30	17~32/0~30
Working Temperature	Outdoor (Cooling/Heating)	°C	-15~50/-20~30	-15~50/-20~30	-15~50/-20~30	-15~50/-20~30
Application Area	Minimum - Maximum	m2	12~18	16~23	24~35	32~47
Container Quantity 20' /40' /40'HO		l	138/284/312	132/274/305	84/180/208	66/137/156
Somewher Quarterly 20 740 740 HU	`		155, 254, 512	102,274,303	04/ 100/ 200	00/13//130

<sup>\*</sup>Leakage in refrigerants causes climate change. Material that has refrigerants with lower global warming potential (GWP) contribute less to global warming if they leak into the atmosphere than materials that have refrigerants higher GWP. This device contains refrigerant liquid has GWP equal to [xxx].

\*In case of the coolant liquid in question leakage into the atmosphere, means that the impact on global warming will be [xxx] times greater than 1 kg CO 2 over a 100-year period. Never interfere with the refrigerant circuit or attempt to disassemble the product yourself, and always consult an expert.

\*Energy consumption according to standard test results. Actual energy consumption will vary depending on how the device is used and where it is located.







ROTA Model Name - Indoor			ROTA REINDEER 12 IDU	ROTA REINDEER 18 IDU	
ROTA Model Na	me - Outdoor		ROTA REINDEER 12 ODU	ROTA REINDEER 18 ODU	
Power supply		V-Ph-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	
Rated Cooling	Capacity	Btu/h	12000(3500~14200)	18000(6600~21400)	
Cooling Power input		w	1140(100~1600)	1550(150~2250)	
Cooling Current		А	5.1(0.4~6.9)	6.7(0.7~9.8)	
Rated Heating	Capacity	Btu/h	13000(3000~16300)	19000(4400~23900)	
Heating Power input		w	1080(160~1710)	1500(220~2350)	
Heating Current		А	4.8(0.7~7.4)	6.5(0.95~10.2)	
	Pdesignc	kW	3,5	5,3	
Seasonal Cooling	SEER	W/W	7.0	7.0	
	Energy Efficiency Class		A++	A++	
	Pdesignh	kW	2,9	4.1	
	SCOP	w/w	4.Oca	4	
Heating(Average )	Energy Efficiency Class		A+	A+	
	Tbiv	°C	-7	-7	
Tol	-	°C	-15	-15	
Max. input consumption		w	2150	2500	
Max. current		А	10	13	
Starting Current		А	1	I	
Compressor	Туре		ROTARY	ROTARY	
Indoor air flow (Hi/Mi/Lo)	1	m3/h	584/477/395	730/500/420	
Indoor sound pressure level (Hi/Mi/Lo/Si)		dB(A)	39/32/26/23	43/33,5/28//	
Indoor sound power level (Hi)		dB(A)	55.0	58.0	
	Dimension(W*D*H)	mm	802x189x297	965x215x319	
Indoor unit	Packing (W*D*H)	mm	875x285x380	1045x305x410	
	Net/Gross weight	Kg	8.6/11.1	10.9/14.2	
Outdoor air flow		m3/h	1800	2100	
Outdoor sound pressure level		dB(A)	56.0	55.5	
Outdoor sound power level		dB(A)	65.0	64.0	
·	Dimension(W*D*H)	mm	720x270x495	805x330x554	
Outdoor unit	Packing (W*D*H)	mm	835x300x540	915x370x615	
	Net/Gross weight	Kg	23.2/25.0	33.5/36.1	
	Туре		R32	R32	
Refrigerant	GWP		675	675	
	Charged quantity	Kg	0.55	1.1	
	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/12.7mm(1/2in)	
Refrigerant piping	Max. refrigerant pipe length	m	25	30	
	Max. difference in level	m	10	20	
Connection wiring	wax. directice in jevel		1.5x5//	1.5x5//	
Plug type			//no-plug	//no-plug	
	1		Remote Control	Remote Control	
Thermostat type	Indoor(cooling/ heating)	°C	17 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30	
Operation temperature	Outdoor(cooling/heating)	~ ~		-15 ~ 50/-15 ~ 24	
Application area	minimum-maximum	m2	-15 ~ 50/-15~24 16 ~ 23	24 ~ 35	
Qty'per 20' /40' /40'HQ		IIIZ	130/276/302	86/174/204	
Annual energy consuption (Cooling / Heating)		kWh/yearl	180 / 991	265 / 1435	
Design load in -10 °C ( P design)	Heating	+	2,9	4,1	
Declared capasity in -10 °C  P design)	Heating	kW	2,687	3,393	
	+	kW	0,213		
Replacement (extra) heating capasity in -10 °C  Annual energy consuption (Cooling / Heating)	Heating	kW		0,707	
(Aegean, Mediterranean Region)	I	kWh/year	180 / 639	265 / 1308	
	P design	kW	2,5	4,4	
Heating (Aegean, Mediterranean Region)	SCOP	W/W	4,73	5,1	
	Energy Efficiency Class		A+++	A+++	

Leskage in refrigerants causes climate change. Material that has refrigerants with lower global warming potential (GWP) contribute less to global warming if they lesk not the atmosphere than materials that have refrigerants higher GWP. This device contains refrigerant legid has GWP equal to [xxx]. In case of the coolant liquid in question leakage into the atmosphere, means that the impain global warming will be [xxx] through the first part of the product yourself, and always consult an expert.

Energy consumption according to standard test results. Actual energy consumption will vary depending on how the device is used and where it is located.







	ROTA Model Name - Indoor		POLAR 24 ID	POLAR 42 ID	POLAR 48 ID
F	ROTA Model Name - Outdoor		POLAR 24 OD	POLAR 42 OD	POLAR 48 OD
Power supply		V-Ph-Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz	220-240V,1Ph,50Hz
Rated Cooling	Capacity	Btu/h	24000(12000~24100)	41300(10000~42000)	48000(12000~52400)
Cooling Power input		w	2340(570~3600)	4400(680~4600)	4900(900~5700)
Cooling Current		А	10.4(2.5~16.0)	19.5(3.1~20.4)	22(5,2~25)
EER		w/w	3.01	2.75	2.87
Heating Capacity		Btu/h	26000(9600~33400)	45000(11500~47000)	55000(14000~60000)
Heating Power input		w	2000(1450~3150)	3900(750~4400)	5100(1000~5700)
Heating Current		А	8.9(6.7~14.0)	17.0(3.4~19.5)	22.5(5.2~25.0)
COP		W/W	3,81	3,38	3,16
	Pdesigno	kW	7.0	12.1	14.1
	SEER	w/w	6.1	5.8	6.1
Seasonal Cooling	Energy Efficiency Class		A++	A+	A++
	Seasonal Space Heating Efficiency (ηs,c)	%			241
	Pdesignh	kW	6.1	8.4	11.0
	SCOP	w/w	4.0	4.2	4.0
Heating(Average )	Energy Efficiency Class		A+	A+	A+
	Seasonal Space Heating Efficiency (ηs,c)	%			157
	Tbiv	°C	-7	-7	-7
	Tol	°C	-15	-15	-15
Max. input consumption		w	4850	5000	6900
Max, current		А	20,0	22,5	29,0
Compressor	Туре		Twin-ROTARY	ROTARY	ROTARY
Indoor air flow (Hi/Mi/Lo)	1	m3/h	990/760/640	1900/1750/1550	2413/2222/2027
Indoor sound pressure level (H	i/Mi/Lo/Si)	dB(A)	39,5/37,5/34,5	52/49/46/40	53/50/48/39,5
Indoor sound power level (Hi)		dB(A)	59	65	67
	Dimension(W*D*H)	mm	405x405x1775	585x405x1830	1935x629x456
Indoor unit	Packing (W*D*H)	mm	2000x510x490	2060x750x550	2055x750x575
	Net/Gross weight	Kg	29,9/38,4	49,75/61,89	59,0/77,0
Outdoor air flow	<u> </u>	m3/h	3500	5100	7500
Outdoor sound pressure level		dB(A)	58,5	64,0	63,0
Outdoor sound power level		dB(A)	68	73	73
·	Dimension(W*D*H)	mm	890x342x673	946x410x810	952x415x1333
Outdoor unit	Packing (W*D*H)	mm	995x398x740	1090x500x885	1095x495x1480
	Net/Gross weight	Kg	44,7/47,9	66,87/71,51	91,5/105,4
	Туре		R32	R32	R32
Refrigerant	GWP		675	675	675
g	Charged quantity	Kg	1,95	2,3	2,9
	Liquid side/ Gas side	mm(inch)	6.35mm(1/4in)/12.7mm(1/2in)	9,52mm(3/8in)/15,9mm(5/8in)	9,52mm(3/8in)/15,9mm(5/
Refrigerant piping	Max. refrigerant pipe length	m	50	55	65
gorone printly	Max, difference in level		25	20	30
Connection wiring	max, dillerence in level	m	1.5x4//	1.0x4//	1.5x4//
Thermostat type	T				
memostat type	Industrial line ( book).		Remote Control	Remote Control	Remote Control
Operation temperature	Indoor(cooling/ heating)	°C	17 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30	17 ~ 32/0 ~ 30
	Outdoor(cooling/heating)	°C	-15 ~ 50/-15 ~ 24	-15 ~ 50/-15 ~ 24	-15 ~ 50/-15 ~ 24

Leakage in refrigerants causes climate change. Material that has refrigerants with lower global warming potential (GWP) contribute less to global warming if they leak into the atmosphere than materials that have refrigerants higher GWP. This device contains refrigerant liquid has GWP equal to [xxx]. In case of the coolant liquid in question leakage into the atmosphere, means that the impact on global warming will be [xxx] times greater than 1 kg CO 2 over a 100-year period. Never interfere with the refrigerant circuit or attempt to disassemble the product yourself, and always consult an expert. "Energy consumption according to standard test results. Actual energy consumption will vary depending on how the device is used and where it is located.







Pov. Cooling Cur	pacity wer Consuption rrent	V-Ph-Hz Btu/h W	220-240V,1Ph,50Hz 12000 1350	
Pov. Coding Cur	wer Consuption	W		
Cooling Cur	rrent		1350	
EEI		А		
<del> </del>	R		5,9	
Ene	H		2,6	
	ergy Efficiency Class		Α	
Cap	pacity	Btu/h	10000	
Pov	wer Consuption	W	1045	
Heating Cur	rrent	Α	5	
со	)P	W/W	2,8	
Ene	ergy Efficiency Class		A+	
Dehumidification		L/h	3,376	
Nominal Power Consuption		W	1450	
Nominal Current		А	8	
Starting Current		А	20	
Compressor Typ	ре		ROTARY	
Tol		°C	-15	
Max, input consumption		W	2150	
Max. current		А	10	
Compressor Typ	ре		ROTARY	
Air flow (Hi/Mi/Lo)		m3/h	420/370/355	
Sound pressure level (Hi/Mi/Lo)		dB(A)	52/51,3/50,6	
Sound power level (Hi)		dB(A)	64	
Power Consuption in Standby Mode		W	0,5	
Тур	ре		R290	
GW	VP		3	
Refrigerant Cha	arged quantity	Kg	0,22	
со	02 quantity	Kg	0,66	
P Design		MPa	2,6/1,0	
Control type			Remote Controller	
Operation temperature (cooling / heating)		°C	17-35/5-30	
Application area (at cooling standard)		m2	16-23	
Din	mension(W*D*H)	mm	467/397/765	
Sizes	cking (W*D*H)	mm	512/442/880	
Net	t/Gross weight	Kg	33,2/37	

"Leakage in refrigerants causes climate change. Material that has refrigerants with lower global warming potential (GWP) contribute less to global warming if they leak into the atmosphere than materials that have refrigerants higher GWP. This device contains refrigerant liquid has GWP equal to [xxxx]. In case of the coolant liquid in question leakage into the atmosphere, means that the impact on global warming will be [xxxx] times greater than 1 kg CO 2 over a 100-year period. Never interfere with the refrigerant circuit or attempt to disassemble the product yourself, and always consult an except. consult an expert.

consult all expert.

Tenergy consumption according to standard test results. Actual energy consumption will vary depending on how the device is used and where it is located.





		CASSETTE 24	CASSETTE 42	CASSETTE 48
		CASSETTE 24 ID	CASSETTE 42 ID	CASSETTE 48 ID
		CASSETTE 24 OD	CASSETTE 420D	CASSETTE 48 OD
Pdesign I	kW	7,0	12,1	14,0
SEER	W/W	6,2	6,1	6,1
Energy Efficiency Class		A++	A++	A++
	%			241
	kW	6,0	9,5	11,0
SCOP	w/w	4,0	4,0	4,0
Energy Efficiency Class		A+	A+	A+
	%			157
	_	-7	-7	-7
	_			12
SCOP	_			5,0
				A++
	8			2
	_			-15
Indeer Unit	_			220-240V.1Ph,50Hz
	_			380-415V.3Ph.50Hz
Outdoor Office	1			48000(12000~54000)
Capacity	_			
				14.07(3.52~15.83)
	-			4650(800~5900)
Operating current	+ -			8.1(1.8~10.2)
Capacity	$\vdash$			55000(14000~59000)
	kW	7.62(2.81-8.94)	13,48(3,37-14,07)	16.12(4.10-17.29)
Electric power	w	1900(610~2700)	3700(750~4250)	4580(900~5500)
Operating current	Α	8.5(3.6~12.1)	16.3(3.4~19)	8.0(1.9~9.5)
Air flow (Hi/Mi/Lo)	m3/h	1247/1118/992	1900/1750/1600	1900/1750/1600
Sound pressure level (Hi/Mi/Lo)	dB(A)	50/47.5/42/29	52.5/50/47.5/40	52.5/50.5/48/40
Sound power level	dB(A)	57	65	65
Sound power level	dB(A)	60	60 63	
Sound pressure level	dB(A)	67	67 71	
Dimension Device (W*D*H)	mm	830x830x205	830x830x287	830x830x287
Packing Device (W*D*H)	mm	910x910x250	910x910x330	910x910x330
Dimension Panel (W*D*H)	mm	950x950x55	950x950x55	950x950x55
Packing Panel (W*D*H)	mm	1035x1035x90	1035x1035x90	1035x1035x90
Net/Gross Weight Device	kg	21,6/25,4	29,3/33,5	29,3/33,5
Net/Gross Weight Panel	kg	6/9	6/9	6/9
	mm	ODΦ25mm	ODΦ25mm	ODΦ25mm
	mm	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)
			Remote Control	
Cooling	8	16~32		16-32
	8			0-30
				ROTARY
	m3/h			7500
				952x415x1333
	-			952x415x1333 1095x495x1480
	+			
Neroloss Weight	Kg			103,7/118,3
Type	$\vdash$	1102	1102	R32
	1			675
Charged quantity  Outdoor sound pressure level		1,5	2,8	2,9
	dB(A)	55.5	56.0	56
	dB(A)	61	62	63
Liquid side/ Gas side	mm(inch)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)	9.52mm(3/8in)/15.9mm(5/8in)
Max. refrigerant pipe length	m	50	75	75
Max. difference in level	m	25	30	30
Max. difference in level Operating temperature range (cooling)	m 8	25 -15~50	30 -15~50	30 -15∼50
	SEER Energy Efficiency Class Seasonal space coding energy efficiency (ns.c) Pdesign S SCOP Energy Efficiency Class Seasonal space heating energy efficiency (ns.c) Design temperature Pdesign S SCOP Energy Efficiency Class Seasonal space heating energy efficiency (ns.c) Design temperature  Indoor Unit Outdoor Unit Capacity Electric power Operating current Capacity Electric power Operating current Air flow (HirMiLo) Sound power level Sound power level Dimension Device (W*D*H) Packing Device (W*D*H) Packing Panel (W*D*H) Net/Gross Weight Device Net/Gross Weight Panel Cooling Heating Type Air flow Dimension (W*D*H) Packing (W*D*H) Packing (W*D*H) Packing Season Se	SEER         WW           Energy Efficiency Class         ***           Seasonal space coding energy efficiency (rps.c)         %           Pdesign S         ***           SCOP         WW           Energy Efficiency Class         ***           Seasonal space heating energy efficiency (rps.c)         %           Design temperature         ***           Pdesign S         ***           SCOP         ***           Energy Efficiency Class         ***           Design temperature         ***           Buth         ***           Outdoor Unit         ***           Chapecity         ***           Electric power         ***           Operating current         A           Capacity         ***           Electric power         ***           Operating current         A           Air flow (HiMMLo)         ***           Sound power level         ***           Sound power level         ***           Sound power level         ***           Sound power level         ***           Sound power level         ***           Sound power level         ***           Sound power level	Petesign I         kW         7,0           SEER         W/W         6,2           Energy Efficiency Class         W/W         6,2           Seasonal space coding energy efficiency (rps,c)         %         4           Potesign S         kW         6,0           SCOP         W/W         4,0           Energy Efficiency Class         kW         6,0           Seasonal space heating energy efficiency (rps,c)         %         -7           Possign Emperature         8         -7           Possign temperature         8         2           Possign temperature         8         2           Energy Efficiency Class         W         6,1           Energy Efficiency Class         W         6,1           Energy Efficiency Class         B         2           Energy Efficiency Class         B         2           Energy Efficiency Class         B         2           Possign Engry Efficiency Class         B         2           Brown         6,3         2           Energy Efficiency Class         B         2           COP         8         2         2           College Temperature         W         1,1 <td>Presign I         NW         7.0         12,1           EER         WW         6.2         6.1           Emery Efficiency Class         WW         6.2         6.1           Emery Efficiency Class         WW         6.2         1           Phesign B         WW         0.0         0.5           SCOP         WW         4.0         0         4.0           Beschald space heading amongs efficiency (rig.s)         %         1         4.0         4.0           Beschald space heading amongs efficiency (rig.s)         %         1.0         1         7.7</td>	Presign I         NW         7.0         12,1           EER         WW         6.2         6.1           Emery Efficiency Class         WW         6.2         6.1           Emery Efficiency Class         WW         6.2         1           Phesign B         WW         0.0         0.5           SCOP         WW         4.0         0         4.0           Beschald space heading amongs efficiency (rig.s)         %         1         4.0         4.0           Beschald space heading amongs efficiency (rig.s)         %         1.0         1         7.7

\*Leakage in refrigorants causes climate change. Material that has refrigerants with lower global warming potential (GWP) contribute less to global warming if they leak into the atmosphere than materials that have refrigerants

higher GWP. This device contains refrigerant liquid has GWP equal to [xxx] In case of the coolant liquid in question leakage into the atmosphere, means that the impagreater than 1 kg CO 2 over a 100-year period. Never interfere with the refrigerant circuit or attempt to disassemble the product yourself, and always consult an expert.







Model			ROTA-DT60
Indoor Model			ROTA-DT60 ID
Outdoor Model			ROTA-DT60 OD
	Pdesign C	kW	15,3
	SEER	w.w	6,1
	Energy Efficiency Class		A++
		%	241
	Seasonal space cooling energy efficiency (ηs,c)		
Avarage	Pdesign H	kW	12,5
	SCOP	w/w	4,0
	Energy Efficiency Class		A+
	Seasonal space heating energy efficiency (ηs,c)	%	157
	Design temperature	⋈	-7
	Tol	⊠	-15
	Pdesign H	kW	12,8
Heating	SCOP	w/w	5,1
(Aegean-Mediterranean region)	Energy Efficiency Class		A+++
	Design temperature	8	2
		+	
Power supply	Indoor Unit	V,Ph,Hz	220-240V,1Ph, 50Hz
	Outdoor Unit	V,Ph,Hz	380-415V,3Ph, 50Hz
	Capacity	Btu/h	52000 (14000~59000)
Cooling		kW	15,24 (4,10~17,29)
-	Operating power	w	5250 (1030~6650)
	Operating current	Α	9.6 (3.1~11.5)
		Btu/h	62000 (15000~70000)
	Capacity	kW	18,17 (4,40~20,52)
Heating	Operating power	w	5150 (950~6600)
	Operating current	A	9,5 (2~11,5)
	Air flow (Hi/Mi/Lo)	m3/h	2600/2210/1820
		+ -	
Indoor Unit	ESP range	Pa	0~160
	Sound pressure level (Hi/Mi/Lo)	dB(A)	52,5/49/47
	Sound power level	dB(A)	66
Outdoor Unit	Sound power level	dB(A)	64
	Sound pressure level	dB(A)	74
	Dimension Device (W*D*H)	mm	1200x874x300
Indoor unit	Packing Device (W*D*H)	mm	1405x915x365
	Net/Gross Weight Device	kg	47,4/56,1
Drainage water pipe diameter		mm	ODΦ25mm
Refrigerant pipes		mm	9,52mm(3/8in)/15,9mm(5/8in)
Control type			Wired Control
Operating temperature		□ □	16~30
Operating temperature	1	+	
Room temperature	Coaling	Ø	16~32
	Heating	×	0-30
Field of application			64~94
Max. input consumption		w	7500
Max. flow		А	14
Compressor	Туре		ROTARY
Gas control type	•		EXV+Capillary
	Air flow	m3/h	7500
	Dimension(W*D*H)	mm	952x415x1333
Outdoor Unit		+	
	Packing (W*D*H)	mm	1095x495x1480
	Net/Gross weight	Kg	107,0/121,2
	Туре	<del>                                     </del>	R32
Refrigerant	GWP	↓	675
	Charged quantity	Kg	3,0
Outdoor sound pressure level		dB(A)	55.5
Outdoor sound power level		dB(A)	61
	Liquid side/ Gas side	mm(inch)	9,52mm(3/8in)/15,9mm(5/8in)
Refrigerant piping	Max. refrigerant pipe length	m	75
- war without age		+	
	Max. difference in level	m -	30
Ambient temperature	Operating temperature range (cooling)	Ø	-15~50
	Operating temperature range (heating)	⊠	-20~24
M polyago in refeigerente c	dimete abance. Material that has refrigen	e alabal we	

Leakage in refrigerants causes climate change. Material that has refrigerants with lower global warming potential (GWP) contribute less to global warming if they leak into the atmosphere than materials that have refrigerants.


higher GWP. This device contains refrigerant liquid has GWP equal to [xoo]. In case of the coolant liquid in question leakage into the atmosphere, means that the impact on global warming will be [xoo] times greater than 1 kg CO 2 over a 100-year period. Never interfere with the refrigerant circuit or attempt to disassemble the product yourself, and always consult an expert.

"Energy consumption according to standard test results. Actual energy consumption will vary depending on how the device is used and where it is located.

9.000-12.000-18.000-24.000









#### 18.000-28.000-36.000-42.000

Multi Wall Mounted Type	ndoor Units		MS 09-ID	MS 12-ID	MS 18-ID	MS 24-ID		
Power supply		V-Ph-Hz	220V-240V,1Ph,50Hz					
	Capacity	kW / Btu/h	2,64 / 9000	3,52 / 12000	5,28 / 18000	7,00 / 24000		
Cooling	Power input	w	20	20	34	62		
	Current	А	0.09	0.09	0.15	0.28		
	Capacity	kW / Btu/h	2,93 / 10000	3,81 / 13000	5,56 / 19000	7,32 / 25000		
Heating	Power input	w	20	20	34	62		
	Current	А	0.09	0.09	0.15	0.28		
Air flow (Hi/Mi/Lo)			520/460/340	600/500/360	840/680/540	980/817/662		
Sound pressure level (Hi/Mi/Lo/	Si)	dB(A)	40/30/26/21	40/34/26/22	44/37/30/25	44.5/42/34.5/28		
Sound power level (Hi)		dB(A)	54	53	55	59		
	Dimension(W*D*H)	mm	805x194x285	805x194x285	957x213x302	1040x220x327		
Indoor unit	Packing (W*D*H)	mm	870x270x360	870x270x360	1035x295x380	1120x405x310		
Indoor drik	Net/Gross weight	Кд	7.5/9.7	7.5/9.7	10/13	12,3/15,8		
	Liquit/Gas Copper Pipe	mm(inch)	Ф6.35(1/4")/Ф9.52/(3/8")	Ф6.35(1/4")/Ф9.52/(3/8*)	Ф6.35(1/4")/Ф12.7(1/2")	Ф9.52(3/8")/Ф15.9(5/8")		
Controller Type			Remote Controller					
Cooling		8	17-32					
Ambient rempiature	Ambient Temprature Heating		0-30					
Operating Tempreature	•	8		17	-30			

Multi Duct Type Indoor U	nits		MD 09-ID	MD 12-ID	MD 18-ID	MD 24-ID	
Power supply		V-Ph-Hz	220V-240V,1Ph,50Hz				
	Capacity	kW / Btu/h	2,64 / 9000	3,52 / 12000	5,28 / 18000	7,04 / 24000	
Cooling	Power input	w	70	70	184	208	
	Current	А	0,42	0,42	1,19	1,35	
	Capacity	kW / Btu/h	2,93 / 10000	3,81 / 13000	5,56 / 19000	7,62 / 25000	
Heating	Power input	w	70	70	184	208	
	Current	А	0,42	0,42	1,19	1,35	
Air flow (Hi/Mi/Lo)			500/340/230	600/480/300	911/706.3/515.2	1229/1035/825.1	
External Static Pressure	Graduated			2	5	-	
Existral Gallet Fleddig	Spacing	Pa	0-40	0-60	0-100	0-160	
Sound pressure level (Hi/Mi/Lo	Si)	dB(A)	40/34.5/27.5	34.5/30.5/29/23	41/38/34/26	49/46/41/27	
Sound power level (Hi)		dB(A)	58	57	58	61	
	Dimension(W*D*H)	mm	700x450x200	700x506x200	880x674x210	1100x774x249	
ndoor unit	Packing (W*D*H)	mm	860x540x275	860x540x285	1070x725x280	1305x805x315	
	Net/Gross weight	Kg	18/22	17.8/21.5	24.4/29.6	32.3/39.1	
Drainage Water Pipe Diameter		mm		00	Φ25		
Liquit/Gas Copper Pipe		mm(inch)	Ф6.35(1/4")/Ф9.52/(3/8")	Ф6.35(1/4")/Ф9.52/(3/8") Ф6.35(1/4")/Ф9.52/(3/8") Ф6.35(1/4")/Ф12.7(1/2")		Ф9.52(3/8")/Ф15.9(5/8")	
Controller Type				Wired 0	Controller		
Ambient Temprature	Cooling	8	17-32	16-32	16-32	16-32	
Ambient rempiature	Heating	В		0-	0-30		
Operating Tempreature	•	10	17-30	16-30	16-30	16-30	

Multi Cassette Type Ir	ndoor Units		MC 12-ID	MC 18-ID	MC 24-ID
Power supply		V-Ph-Hz		220V-240V,1Ph,50Hz	
	Capacity	kW / Btwh	3,52 / 12000	5,28 / 18000	7,04 / 24000
Cooling	Power input	w	64	64	70
	Current	A	0,38	0,38	0,42
	Capacity	kW / Btu/h	3,81 / 13000	5,57 / 19000	7,60 / 26000
Heating	Power input	w	64	64	70
	Current	A	0,38	0,38	0,42
Air flow (Hi/Mi/Lo)	•	m3/h	620/510/420	720/620/500	1247/1118/992
Sound pressure level (Hi/Mi	(Lo/Si)	dB(A)	41/36/33/25.5 43/39.5/35.5/29 50/		
Sound power level (Hi)		dB(A)	56	57	57
	Dimension(W*D*H)	mm	570x570x260	570x570x260	830x830x205
	Packing (W*D*H)	mm	662x662x317	662x662x317	910x910x250
ndoor unit	Dimension Panel(W*D*H)	mm	647x647x50	647x647x50	950x950x55
nggor driit	Packing Panel(W*D*H)	mm	715x715x123	715x715x123	1035x1035x90
	Net/Gross Weight	Кд	16.3/20.4	16/20.6	21.6/25.4
	Net/Gross Weight Panel	Kg	2.5/4.5	2.5/4.5	6.Eyl
Drainage Water Pipe Diamet	er	mm		ODФ25mm	
Liquit/Gas Copper Pipe		mm(inch)	Φ6.35(1/4")/Φ9.52/(3/8")	Ф6.35(1/4")/Ф12.7(1/2")	Ф9.52(3/8")/Ф15.9(5/8")
Controller Type				Remote Controller	-
Ambient Terrenture	Cooling	10	16-32	16-32	16-30
Ambient Temprature	Heating	10		0-30	•



**MULTI SERI** 

18.000-28.000-36.000-42.000

Multi Outdoor Units			M2-18 OD	M3-28 OD	M4-36 OD	M5-42 OD
ower supply		V-Ph-Hz		220V-240V	/,1Ph,50Hz	
	Capacity	kW / Btu/h	18000(7800~19500)	27000(10850~28000)	36000(12430~37000)	42000(10300~42000)
Cooling	Power input	w	1635(690~2000)	2450(290~3100)	3300(330~4250)	3810(280~4650)
	Current	Α	7.3(3.2~9.0)	11.2(2.0~13.5)	15.0(1.5~18.5)	16(1.4~20.7)
ER		w/w	3,23	3,23	3,20	44986,00
	Capacity	kW / Btu/h	19000 ( 8200~19600)	28000(7800~29000)	37000(9730~41000)	42000(11800~42000)
leating	Power input	w	1500(600~1780)	2210(370~2900)	2760(470~4210)	3300(650~3800)
	Current	Α	6.6(2.80~7.95)	10.1(2.4~13)	12.1(2.1~18.4)	14.6(3.0~16.6)
OP		w/w	3,71	3,71	3,93	26724,00
	Pdesigno	kW	5,3	7,9	10,6	12,3
easonal Cooling	SEER	w/w	6,1	6,1	6,2	6,1
	Energy Efficiency Class		A++	A++	A++	A++
	Pdesignc	kW	4,8	5,6	9,0	9,5
eating (Average)	SCOP	w/w	3,8	4,0	3,8	3,5
eating (Average)	Energy Efficiency Class		А	A+	A	А
	Design Heating	0	-7	-7	-7	-7
	Pdesignc	kW	5,0	6,1	9,8	10
acting (Marmor)	SCOP	w/w	5,1	5,1	5,2	4,9
leating (Warmer)	Energy Efficiency Class		A+++	A+++	A+++	A++
	Design Heating	0	2	2	2	2
ol .		0	-15	-15	-15	-15
lax. Input Consumption		w	3050	4100	4600	4700
Max. Input Current		А	13	18	21,5	22
Compressor Type			ROTARY	Twin-ROTARY	ROTARY	ROTARY
ir flow		m3/h	2100	3000	4000	3850
ound pressure level		dB(A)	54	58	61	64
ound power level		dB(A)	65	68	67	69
Sas Control Type				EXV+C	Capillary	
limension(W*D*H)		mm	805*330*554	890*342*673	946x410x810	946x410x810
acking (W*D*H)		mm	915*370*615	1030*438*750	1090x500x885	1090x500x885
let/Gross weight		kg	35/38	48/51,8	68,8/75,6	74,1/79,5
	Туре			R	32	
tefrigerant	GWP			6	75	
	Charged quantity	Kg	1,25	1,85	2,1	2,9
	Liquit/Gas Copper Pipe	mm(inch)	2x6.35mm(2x1/4in)/2x9.52mm( 2x 3/8in)	3x6.35mm(3x1/4in)/3x9.52mm(3x 3/8in)	4x6.35mm(4x1/4in)/3x9.52mm+ 1 x12.7mm(3x3/8in+1x1/2in)	5x6.35mm(5x1/4in)/4x9.52 1 x12.7mm(4x3/8in+1x1/
	Max, Length for All Rooms	m	40	60	80	80
efrigerant Pipes	Max, Length for 1 Indoor Unit	m	25	30	35	35
	Maximum height difference between indoor unit and outdoor unit	m	15	15	15	15
	Maximum height difference between indoor units	m	10	10	10	10
	Cooling	8	-15 - 50	-15 - 50	-15 - 50	-15 - 50
mbient Temprature						

Leakage in refrigerants causes climate change. Material that has refrigerants with lower global warming potential (GWP) contribute less to global warming if they leak into the atmosphere than materials that have refrigerants higher GWP. This device contains refrigerant liquid has GWP equal to [pox]. In case of the coolant liquid in question leakage into the atmosphere, means that the impact on global warming will be [pox] times greater than 1 kg CO 2 over a 100-year period. Never interfere with the refrigerant circuit or attempt to disassemble the product yourself, and always consult an expert.

"Energy consumption according to standard test results. Actual energy consumption will vary depending on how the device is used and where it is located.

MULTIOUTDOORS COMBINATION	LENGTH	HEIGHT DIFFERENCE
1 OD + 2 ID	40 m	15 m
1 OD + 3 ID	60 m	15 m
1 OD + 4 ID	80 m	15 m
1 OD + 5 ID	80 m	15 m



OCTOPUS MULTI SERI

18.000-28.000-36.000-42.000

MULTI ONE-WA	Y CASETTE INDOOR UNITS		MC1-09	MC1-12	MC1-18	MC1-24
Power supply		V,Hz,Ph	220-240V, 50Hz, 1Ph	220-240V , 50Hz , 1Ph	220-240V , 50Hz , 1Ph	220-240V, 50Hz, 1Ph
	Capacity	Btu/h	9000	12000	18000	24000
Cooling	Input	W	50	50	80	80
	Rated current	Α	0,3	0,3	0,4	0,4
	Capacity	Btu/h	10000	13000	19000	24000
Heating	Input	W	50	50	80	80
	Rated current	Α	0,3	0,3	0,4	0,4
Indoor air flow		m3/h	470/360/270	500/420/300	920/800/690	1000/870/730
Indoor sound pressu	ire level	dB(A)	42/37/34	44/39/34	45/41/35	45/42/37
Indoor sound power	level	dB(A)	55	56	58	60
	Dimension (W x Dx H) (body)	mm	880x450x130	880x450x130	1180x450x130	1180x450x130
	Packing (W x Dx H) (body)	mm	1115x555x240	1115x555x240	1415x555x240	1415x555x240
Indoor unit	Net/Gross weight(body) (body)	kg	14.7/18.5	14.6/18.5	17.9/22.4	17.9/22.4
indoor drift	Dimension (W x Dx H) (panel)	mm	1180x500x34	1180x500x34	1480x500x34	1480x500x34
	Packing (W x Dx H) (panel)	mm	1280x626x136	1280x626x136	1580x626x136	1580x626x136
	Net/Gross weight (panel)	kg	4.4/7.9	4.4/7.9	5.3/9.4	5.3/9.4
Drainage water pipe	dia.	mm	ODΦ25mm	ODΦ25mm	ODΦ25mm	ODΦ25mm
Refrigerant piping	Liquid side/ Gas side	mm	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/9.52mm(3/8in)	6.35mm(1/4in)/12.7mm(1/2in)	6.35mm(1/4in)/12.7mm(1/2in)
Contro <b>ll</b> er			Remote Control	Remote Control	Remote Control	Remote Control
Operation temperatu	ıre	⊠	16~30	16~30	16~30	16~30
Room temperature	Cooling	⊠	16~32	16~32	16~32	16~32
Noon temperature	Heating	×	0~30	0~30	0~30	0~30





### Flexible branch header Lineup

Model	1 to 2 branch header DXFQT2-02	1 to 3 branch header DXFQT3-02	1 to 4 branch header DXFQT4-02	1 to 5 branch header DXFQT5-02	1 to 6 branch header DXFQT6-02
Görünüş	J J				

# OCTOPUS Mini VRF Series

Outdoor Units
Capacity range:

28/36/42/48/56/60 Btu/h (6 models)







28/36kBtu/h

42/48/56kBtu/h

One-way Cassette

Capacity range:

06/07/09/12/15/18/24k Btu/h (7 models)



Four-way Cassette
Capacity range:
09/12/15/18/24/28/32/36/40/48/56k
Btu/h (11 models)



#### **Compact Four-way Cassette**

Capacity range:

05/07/09/12/15k Btu/h (5 models)



## Medium Static Pressure Duct

Capacity range:

07/09/12/15/18/24/28/32/40/48/56k Btu/h (11 models)



#### Medium Static Pressure Duct (Arc Series)

Capacity range:

05/07/09/12/15/18/24k Btu/h (7 models)



#### **High Static Pressure Duct**

Capacity range:

24/28/32/40/48/56k Btu/h (6 models)



#### Wall Mounted

Capacity range:

07/09/12/15/18/24/28/32k Btu/h

(8 models)



#### Celling / Floor

Capacity range:

12/15/1824/28/32/40/48k Btu/h (8 models)



Note: Octopus Mini Vrf indoor units can Connect to Octopus Mini Vrf outdoor units only.

## **Outdoor Units Specifications**

Model			OCTOPUS V-28 OD	OCTOPUS V-36 OD	OCTOPUS V-42 OD	OCTOPUS V-48 OD	OCTOPUS V-56 OD	OCTOPUS V-60 OD		
Power Supply					220-240	V~ 50Hz				
Caalina Canasitu		kBtu/h	24(5~27)	30(6~34)	42	47	52	59		
Cooling Capacity		kW	7,2(1,5-8)	9(2-10)	12.3	14	15.5	17.5		
kBtu/h 24,5(5~30) 30(7~41) 47 54 59							59	64		
Heating Capacity						19				
Connectable	Total Capacity	·		45 ~ 130% of outdoor unit capacity						
Indoor Unit	Quantity	Minimum	1	1	1	1	1	1		
	Quantity	Maximum	4	6	7	8	9	9		
C	Туре				DC In	verter				
Compressor	Quantity		1							
Fan Motor	Туре				DC m	otor				
Tarriotor	Quantity					1				
Refrigerant Type	•				R4	10A				
Liquid/Gas Pipe			Ф9,53/Ф15,9	Ф9,53/Ф15,9	Ф9,53/Ф15,9	Ф9,53/Ф15,9	Ф9,53/Ф19,1	Ф9,53/Ф19,1		
Net Dimensions (V	/xHxD)		910x712x426	910x712x426	950x840x440	950x840x440	950x840x440	1040x865x523		
Net Dimensions (V	/xHxD)		1045x810x485	1045x810x485	1025x950x510	1025x950x510	1025x950x510	1120x980x560		
Operating Temper	ature Range				Soğutma: -15~5	5, Isıtma: -15~27				





#### OCTOPUS VC-1\*\*ID

-	Model	06	07	09		15	18	24
THE PARTY OF THE P	Power Supply		-	1	phase, 220-240V, 50	Hz		
	Cooling Capacity (kW/kBtu/h)	1.8/6	2.2/7	2.8/9	3.6/12	4.5/15	5.6/19	7.1/24
	Heating Capacity (kW/kBtu/h)	2,2/7	2,6/8	3,2/10	4/13	5/17	6,3/21	8/27
One-Way Cassette	Indoor Air Flow (m3/h)	523/404/275	523/404/275	573/456/315	573/456/315	693/600/476	792/688/549	933/749/592
	Sound Pressure Level (dB(A))	37/34/30	37/34/30	39/37/34	40/38/34	41/39/35	42/40/36	44/41/37

#### OCTOPUS VC-4\*\*ID

Q COL T	Model	09	12	15	18	24	28	32	36	40	48	56
Common	Power Supply											
	Cooling Capacity (kW/kBtu/h)	2.8/9	3.6/12	4.5/15	5.6/19	7.1/24	8/27	9/30	10/34	11.2/38	14/47	16/54
C ammin )	Heating Capacity (kW/kBtu/h)	3.2/10	4/13	5/17	6.3/21	8/27	9/30	10/34	11.1/37	12.5/42	16/54	18/61
Four-Way Cassette	Indoor Air Flow (m3/h)	764/638/554	764/638/554	905/740/651	905/740/651	950/767/663	1200/1021/789	1332/1129/908	1651/1304/1127	51/1304/1	1658/1335/1130	2100/1950/1800 /1750/1600 /1450/1350
S	Sound Pressure Level (dB(A))	32/31/30	32/31/30	36/34/33	36/34/33	38/36/35	42/39/37	43/39/38	45/42/40	45/42/40	46/41/39	46/44/42/41 /39/38/37

#### OCTOPUS VC-4\*\*C ID

G	Model	05	07	09		15				
	Power Supply		1 phase, 220-240V, 50Hz							
	Cooling Capacity (kW/kBtu/h)	1.5/5	2.2/7	2.8/9	3.6/12	4.5/15				
	Heating Capacity (kW/kBtu/h)	1.7/5	2.4/8	3.2/10	4/13	5/17				
Compact Four-Way	Indoor Air Flow (m3/h)	400/283/208	414/313/238	414/313/238	521/409/314	521/409/314				
Cassette	Sound Pressure Level (dB(A))	35/33/23	36/33/23	36/33/23	42/36/29	42/36/29				

#### OCTOPUS VD\*\*ID

	Model	07	09	12	15	18	24	28	32	40	48	56
	Power Supply											
	Cooling Capacity (kW/kBtu/h)	2.2/7	2.8/9	3.6/12	4.5/15	5.6/19	7.1/24	8/27	9/30	11.2/38	14/47	16/54
	Heating Capacity (kW/kBtu/h)	2.6/8	3.2/10	4/13	5/17	6.3/21	8/27	9/30	10/34	12,5/42	15,5/52	17/58
	Indoor Air Flow (m3/h)	550/397/309	550/397/309	605/442/351	800/573/479	800/573/479	985/738/630	1345/1165/1013	1345/1165/1013	00/1556/1	1905/1636/1400	3620/3044/2744
Medium Static Pressure Duct	External static pressure (Pa)			10(0	~ 30)			20(1	0 ~ 50)	10(10 ~ 80	40(10 ~ 100)	50(50 ~ 196)
	Sound Pressure Level (dB(A))	32/24/21	31/24/21	35/28/24	36/29/26	36/29/27	36/30/27	45/40/37	45/40/37	48/42/38	48/43/39	54/52/50

#### OCTOPUS VD\*\*ARC ID

	Model	07	09	12	15	18	24	28		
***	Power Supply		1 phase, 220-240V, 50Hz							
	Cooling Capacity (kW/kBtu/h)	1.5/5	2.2/7	2.8/9	3.6/12	4.5/15	5.6/19	7.1/24		
	Heating Capacity (kW/kBtu/h)	1.8/6	2.5/8	3.2/10	4/13	5/17	6.3/21	8/27		
Medium Static	Indoor Air Flow (m3/h)	340/330/320/ 310/300/295/290	370/345/335/ 320/310/300/295	460/430/410/ 380/350/320/300	605/550/500/ 450/410/360/320	800/720/690/ 625/560/515/435	900/780/745/ 655/580/560/470	1145/1000/930/840 /750/665/580		
Pressure Duct (Arc Series)	External static pressure (Pa)				10(10 ~ 50)					
	Sound Pressure Level (dB(A))	27/25.5/24/ 23/22/21/20	28/27/26/ 25/24/23/22	30/29/28/ 27/26/25/24	30/29/28/ 27/26/25.5/25	34/33/32/ 30/29/28/26	36/34/33/ 32/31/30/28	37/35/34/ 32.5/31/30/29		

#### OCTOPUS VD\*\*H ID

	Model	24	28	32	40	48	56			
UI	Power Supply	1 phase, 220-240V, 50Hz								
	Cooling Capacity (kW/kBtu/h)	7.1/24	2.2/7	2.8/9	3.6/12	4.5/15	5.6/19			
	Heating Capacity (kW/kBtu/h)	8/27	2.5/8	3.2/10	4/13	5/17	6.3/21			
High Static Pressure Duct	Indoor Air Flow (m3/h)	1395/1315/ 1248/1204	370/345/335/ 320/310/300/295	460/430/410/ 380/350/320/300	605/550/500/ 450/410/360/320	800/720/690/ 625/560/515/435	900/780/745/ 655/580/560/470			
	External static pressure (Pa)	25(25 ~ 196)	37(37 ~ 196)	37(37 ~ 196)	50(50 ~ 196)	50(50 ~ 196)	50(50 ~ 196)			
	Sound Pressure Level (dB(A))	48/46/44/43	48/46/45/43	52/49/47/45	52/49/47/46	53/50/48/46	54/52/50/48			

#### OCTOPUS VS\*\* ID

	Model	07	09	12	15	18	24	28	32
	Power Supply	1 phase, 220-240V, 50Hz							
	Cooling Capacity (kW/kBtu/h)	2.2/7	2.8/9	3.6/12	4.5/15	5,6/19	7.1/24	8/27	9/30
	Heating Capacity (kW/kBtu/h)	2,4/8	3,2/10	4/13	5/17	6,3/21	8/27	9/30	10/34
Wall Mounted	Indoor Air Flow (m3/h)	446/429/424/409/ 394/382/373	457/445/433/421/ 419/410/402	447/429/399/369/ 339/333/303	648/618/582/563/ 546/505/476	798/764/723/691/ 665/627/595	1240/1171/1107/ 1045/976/914/869	1248/1194/1119/ 1056/993/914/863	1427/1403/1303/1232/ 1186/1096/1043
	Sound Pressure Level (dB(A))	34/33/33/32 /32/31/31	33/33/32/32 /31/31/31	36/35/34/33 /32/32/32	37/36/34/34 /33/32/31	42/41/40/39 /38/37/36	48/47/45/44 /42/39/38	48/47/45/43 /42/39/38	52/51/50/49 /47/45/43

#### OCTOPUS VF\*\* ID

0C10P05 V	F ID								
	Model	12	15	18	24	28	32	40	48
0-	Power Supply	1 phase, 220-240V, 50Hz							
Bernell British	Cooling Capacity (kW/kBtu/h)	3.6/12	4.5/15	5.6/19	7.1/24	8/27	9/30	11.2/38	14/47
	Heating Capacity (kW/kBtu/h)	4/13	5/17	6.3/21	8/27	9/30	10/34	12.5/42	15/51
Ceiling / Floor	Indoor Air Flow (m3/h)	650/570/500	800/600/500			1200/900/700		1980/1860/1730	
	Sound Pressure Level (dB(A))	40/38/36		43/41/38		45/43/40		47/45/42	

Notes:1. The full model name can be obtained by substituting the asterisk in the model name format given above the table with the model index given in the table.





# Heat Pump Monoblock

MODEL Power supply(V/Ph/Hz)			ROTA HP-MB 8 220-240/1/50	ROTA HP-MB 10 220-240/1/50	ROTA HP-MB 12 220-240/1/50	ROTA HP-MB 16 220-240/1/50
Power supply(V/Pn/Hz)	Capacity	w	8400	10000	12200	16000
	Rated input	w	1663	2128	2490	3556
Heating A7W35	COP	٠	5,05	4,70	4,90	4,50
	Capacity	w	8500	10200	12500	16200
	Rated input	w	2237	2795	3378	4696
Heating A7W45	COP	_	3,80	3,65	3,70	3,45
	Capacity	W	8200	9400	12000	16000
	Rated input	W	2603	3032	4000	5614
Heating A7W55	COP		3,15	3,10	3,00	2,85
	Capacity	W	7100	8200	12300	14500
	Rated input	W	1797	2158	3417	4462
Heating A2W35	COP	•	3,95	3,80	3,60	3,25
	Capacity	W	7500	8500	12000	14300
	Rated input	W	2459	2881	4138	5296
Heating A2W45	COP	•	3,05	2,95	2,90	2,70
	Capacity	W	7600	8400	12000	13500
	Rated input	W	2815	3170	5106	5870
Heating A2W55	COP	•	2,70	2,65	2,35	2,30
	Capacity	W	7100	8000	11600	13500
	Rated input	W	2254	2667	4070	5000
leating A-7W35	COP	_	3,15	3,00	2,85	2,70
	Capacity	W	6800	7400	11500	13500
	Rated input	W	2720	3083	4792	6000
leating A-7W45	COP		2,50	2,40	2,40	2,25
	Capacity	w	6600	7200	10800	12800
	Rated input	w	3143	3512	5143	6244
leating A-7W55	COP	-	2,10	2,05	2,10	2,05
🗸	Capacity	w	8300	10000	12200	15400
	Rated input	w	1711	2326	2652	3667
Cooling A35W18	EER	٠	4,85	4,30	4,60	4,20
, coming , co 11 10	Capacity	w	7400	9000	11600	14000
	Rated input	w	2349	3103	3742	4828
Cooling A35W7	EER	· · ·	3,15	2,90	3,10	2,90
	Water outlet at	35°C	A+++	A+++	A+++	A+++
easonal space heating energy efficiency class	Water outlet at	55°C	A++	A++	A++	A++
leasonal space healing energy eniciency class	vvaler outlet at	35°C	6,94	7,05	6,63	6,46
	Warmer climate	55°C	4,74	4,91	4,55	4,72
	warrier climate	35°C	5,18	5,12	5,08	4,84
	Average climate	55°C	3,67	3,71	3,62	3,59
	Average climate	35°C	4,44	4,44	4,30	4,35
SCOP	Colder climate	55°C	3,02	3,14	3,23	3,18
SCOP	Water outlet at 7°C	33 C				
SEED.			5,19 8,09	5,08 8,31	5,07	5,11 7,49
SEER	Water outlet at 18°C	- J-D	63	65	7,79 70	7,49
	Heating A7W35	dB				
	Heating max	dB	66	68	74	74
	Heating slince mode 1	dB	61	63	66	67
	Heating slince mode 2	dB	58	60	64	64
	Cooling A35W18	dB	63	65	69	71
	Cooling max	dB	66	68	74	74
) I I IO	Cooling slince mode1	dB	61	63	66	67
Sound power level2	Cooling slince mode2	dB	58	60	63	64
compressor	Туре		DC twin rotary	DC twin rotary	DC twin rotary	DC twin rotary
	Туре		DC motor	DC motor	DC motor	DC motor
	Number	1	1	1	5200	1 5200
an	Air flow	m3/h	4500	4500	5200	5200
kir side heat exchanger	Туре		Fin coil	Fin coil	Fin coil	Fin coil
hrottle	Туре				pansion valve	
t of the count	Type		R32	R32	R32	R32
Refrigerant	Charged volume	kg	1,25	1,25	1,80	1,80
Vater side heat exchanger	Туре		Plakalı	Plakalı	Plakalı	Plakalı
Rated water flow	m3/h		1,44	1,72	2,10	2,75
Vater flow range	m3/h		0.40~1.65	0.40~2.10	0.70~2.50	0.70~3.00
	Туре		DC	DC	DC	DC
Vater pump	Maximum pump head	m	9	9	9	9
	Volume	L	5	5	5	5
xpansion vessel	Maximum working pressure	bar	8	8	8	8
safety valve	MPa		0.3	0.3	0.3	0.3
low switch	m3/h		0.36	0.36	0.6	0.6
Vater side connection			G1"BSP	G1"BSP	G5/4"BSP	G5/4"BSP
Jnit dimension (W×H×D)		mm	865×1040×410	865×1040×410	865×1040×410	865×1040×410
Packing dimension (W×H×D)		mm	970×1190×560	970×1190×560	970×1190×560	970×1190×560
let weight		kg	87	87	106	106
Gross weight		kg	103	103	122	122
	Cooling	°C	-5~43	-5~43	-5~43	-5~43
	Heating	°C	-25~35	-25~35	-25~35	-25~35
	DUBA	°C	-25~43	-25~43	-25~43	-25~43
Ambient temperature range	DHW					
Ambient temperature range	Cooling	°C	5~25	5~25	5~25	5~25
Ambient temperature range		_		5~25 25~65	5~25 25~65	5~25 25~65

# This Technology Will Set Your Mood







www.rotaclimate.com



